

Line Up and Punch Out!



SLUG-SPLITTER^{SC}™

With the new Greenlee Slug-Splitter SC™, the tool does the work...

Introducing the upgraded Greenlee Slug-Splitter SC™ Knockout. Punch through stainless steel in less time and with less potential for errors or alignment problems. What's changed with the new knockout? If you're interested in making sure your holes are perfectly centered, we've added a self-centering feature. This new feature greatly simplifies conduit hole and pilot device alignment. Just




tighten down the punch on your draw stud and let our new punch center itself on the pilot hole. No more trying to line up the die alignment marks in poor lighting conditions or drawing crosshairs on the box to ensure alignment. Greenlee has once again given you a tool designed to make your job easier.

PRODUCT FEATURES

- Save time and ensure accuracy! Self-centering punch aligns itself on pilot hole.
- No need to draw crosshairs or line up die alignment marks.
- Punch 16 gauge stainless steel with a ratchet driver.
- Unique, patent pending punch profile also splits slugs for easier slug removal.



ORDERING INFORMATION

| PUNCH | | DIE | | | | | | | | | | | DRAW STUDS | | |
|---|---------------------|---|-----------|--------|------|-----|-----|-----------------------------|-------------------|------------|-----------------|-------|---|--|--|
|  | |  | | | | | | | | | | |  | | |
| PUNCH CAT./UPC NO. | DIE CAT./UPC NO. | CONDUIT & PIPE | HOLE SIZE | | | | | CAPACITY STAINLESS STEEL | | DRAW STUDS | | | | | |
| | | | ACTUAL | | PG | ISO | GA. | (MM) | HYDRAULIC DRIVERS | | RATCHET DRIVER* | | | | |
| | | | Ø (INCH) | Ø (MM) | | | | | 7804/7904 | 7646/7625 | 1904 | | | | |
| 28154 | 28155 | 1/2" | 7/8 | .885 | 22.5 | 16 | — | 10 | 3.5 | 29451 | 29451 | 30227 | | | |
| 28156 | 28157 | 3/4" | — | 1.115 | 28.3 | 21 | — | 10 | 3.5 | 31872 | 29452 | 12098 | | | |
| 36490 | 36489 | — | 1-7/32 | 1.210 | 30.5 | — | — | 10 | 3.5 | 31872 | 29452 | 12098 | | | |
| 28158 | 28159 | 1" | 1-11/32 | 1.362 | 34.6 | — | — | 10 | 3.5 | 31872 | 29452 | 12098 | | | |
| 28160 | 28161 | 1-1/4" | 1-11/16 | 1.701 | 43.2 | — | — | 10 | 3.5 | 31872 | 29452 | 12098 | | | |
| 28162 | 28163 | 1-1/2" | 1-15/16 | 1.951 | 49.6 | — | — | 10 | 3.5 | — | 29452 | 12098 | | | |
| 28165 | 28166 | 2" | 2-3/8 | 2.416 | 61.5 | — | — | 10 | 3.5 | — | 29452 | 12098 | | | |

* 16 ga. stainless steel capacity with ratchet driver.

DISTRIBUTED BY

CSC Industrial

Ph: 915-613-1145 Fax: 915-760-4832
www.cscindustrial.com



GREENLEE®

A Textron Company

USA 800-435-0786 Fax: 800-451-2632
815-397-7070 Fax: 815-397-1865
Canada 800-435-0786 Fax: 800-524-2853
International +1-815-397-7070 Fax: +1-815-397-9247

4455 Boeing Drive • Rockford, IL 61109-2988 • USA • 815-397-7070
©2004 Greenlee Textron Inc. • An ISO 9001 Company • Printed in USA
Greenlee Textron Inc. is a subsidiary of Textron Inc.

www.greenlee.com

MA-4608 09/04